# MKS SERIES ULTRASONIC CLEANING MACHINE CATALOG 30-Adjustable Adjustable **Noise** Insulation Industrial Handle Temperature Head: Time Reduction

# ULTRASONIC CLEANING MACHINE (MKS SERIES)



# **Models and Specifications:**

Model	Capa city	Ultrasonic Power	Heater Power	Tank Size	Machine Outer Dimension	Packaging Size	Gross Weight	Box Outer Dimension	Total Weight	Frequency
	L	W	W	L x W x H (mm)	LxWxH (mm)	L x W x H (mm)	KG.	LxWxH (mm)	KG.	
			500	300x240x200	400x300x380	430x370x490	14.0	without wooden packaging	14.0	28KHZ/40KHZ
										68KHZ
MKS-060AL	14L	360								80KHZ
										120KHZ
										200KHZ
MKS-080AL	20L	480 500		330x300x200	430x350x380	460x430x490	16.5	without wooden packaging	16.5	28KHZ/40KHZ
										68KHZ
			500							80KHZ
										120KHZ
										200KHZ
	30L	600	500	500×300×200	600×350×380	630×430×480	22.0	Wooden packaging	22.0	28KHZ/40KHZ
										68KHZ
MKS-100AL										80KHZ
										120KHZ
										200KHZ
MKS-120AL	38L	38L 720 100		1000 500×300×250	600×350×480	640×440×560	32.0	Wooden packaging 720×520×790 (1pc)	45.0	28KHZ/40KHZ
			1000							68KHZ
										80KHZ
										120KHZ
										200KHZ

Model	Capacity	Ultrasonic Power	Heater Power	Tank Size	Machine Outer Dimension	Packaging Size	Gross Weight	Box Outer Dimension	Total Weight	Frequency
	L	W	W	LxWxH (mm)	L x W x H (mm)	L x W x H (mm)	KG.	LxWxH(mm)	KG.	
		1080 1000	1000	550×350×300	650×400×580	710×520×650	36.0	Wooden Packaging 720×520×790 (1pc)	51.0	28KHZ/40KHZ
MKS-180AL										68KHZ
	58L									80KHZ
										120KHZ
										200KHZ
MKS-240AL	78L	1440 2000		000 550×400×350	650×450×620	710×550×680	45.0	Wooden Packaging 720×520×790 (1pc)	68.0	28KHZ/40KHZ
			2000							68KHZ
										80KHZ
										120KHZ
										200KHZ
MKS-360AL	130L	130L 2160 300			750×500×720	830×580×820	68.0	Wooden Packaging 880×630×870 (1pc)	80.0	28KHZ/40KHZ
										68KHZ
			3000	650×450×450						80KHZ
										120KHZ
										200KHZ

### **Industrial Series**



#### Feature:

- 1, Time set: 0~30 minutes mechanical timer
- "2, Temperature set: 20~80°Cmechanical heater"
- 3, Material: good quality stainless steel
- 4, Feature: purge tank molded by punch, without any gap
- "5, Drainage system: all the styles were installed G1 big caliber drainage ball valve."
- 6, Heat dissipation: all the styles were installed heat dissipation fans.
- 7, Power control: 40~100% power control
- 8, Certification: CE,EMC,ROHS,FCC



Product Type: MKS-060AL	Ultrasound frequency: 40 / 28KHz
Liner material: SUS304t2.0mm	Capacity: 14L
Time control: digital control 0-30 minutes	Ultrasound power: 360W6 head
Heating power: 500W (cast aluminum heating plate)	Liner size: 300 * 240 * 200MM
Packing size: 430 * 370 * 490M	Product Size: 400 * 300 * 380MM
G.W: 14kg	N.W: 12Kg
Power: AC100-120v, 50 / 60HzAC220-240V, 50 / 60Hz	Power adjustment range: 100-240W



# Model: MKS-080AL

430mm x 350mm x 380mm



Product Type: MKS-080AL	Ultrasound frequency: 40/28KHz
Liner material: SUS304t2.0mm	Capacity: 20L
Time control: digital control 0-30 minutes	Ultrasound power: 480W 8head
Heating power: 500W (cast aluminum heating plate)	Liner size: 330 * 300 * 200MM
Packing size: 460 * 430 * 490M	Product Size: 430 * 350 * 380MM
G.W: 16.5kg	N.W: 15Kg
Power: AC100-120v, 50 / 60HzAC220-240V, 50 / 60Hz	Power adjustment range: 190-480W



# **Model: MKS-100AL**

600mm x 350mm x 380mm



Product Type: MKS-100AL	Ultrasound frequency: 40/28KHz
Liner material: SUS304t2.0mm	Capacity: 30L
Time control: Digital control 0-30 minutes	Ultrasound power: 600W 10head
Heating power: 500W (cast aluminum heating plate)	Liner size: 500 * 300 * 200MM
Packing size:	Product Size: 600 * 350 * 380MM
G.W: 16.5kg	N.W: 15Kg
Power: AC100-120v, 50 / 60HzAC220-240V, 50 / 60Hz	Power adjustment range: 240-600W



# **Model: MKS-120AL**

600mm x 350mm x 480mm



Product Type: MKS-120AL	Ultrasound frequency: 40/28KHz
Liner material: SUS304t2.0mm	Capacity: 38L
Time control: 0-30 minutes of digital control	Ultrasound power: 720W 12head
Heating power: 1000W (aluminum heating plate)	Liner size: 500 * 300 * 250MM
Packing size: 640 * 440 * 560M	Product Size: 600 * 350 * 480MM
G.W: 45kg	N.W: 42Kg
Power: AC100-120v, 50 / 60HzAC220-240V, 50 / 60Hz	Power adjustment range: 280-720W



### **Model: MKS-180AL**

650mm x 400mm x 580mm



Product Type: MKS-180AL	Ultrasound frequency: 40/28KHz
Liner material: SUS304t2.0mm	Capacity: 58L
Time control: 0-30 minutes of digital control	Ultrasound power: 1080W 18head
Heating power: 1000W (aluminum heating plate)	Liner size: 550 * 350 * 300MM
Packing size: 710 * 520 * 560M	Product Size: 650 * 400 * 580MM
G.W: 51kg	N.W: 48.5Kg
Power: AC100-120v, 50 / 60HzAC220-240V, 50 / 60Hz	Power adjustment range: 450-1080W



### **Model: MKS-240AL**

650mm x 400mm x 580mm



Product Type: MKS-240AL	Ultrasound frequency: 40/28KHz
Liner material: SUS304t2.0mm	Capacity: 78L
Time control: digital control 0-30 minutes	Ultrasound power: 1440W 24head
Heating power: 2000W (aluminum heating plate)	Liner size: 550 * 400 * 350MM
Packing size: 710 * 550 * 680M	Product Size: 650 * 450 * 620MM
G.W: 51kg	N.W: 48.5Kg
Power: AC100-120v, 50 / 60HzAC220-240V, 50 / 60Hz	Power adjustment range: 580-1440W




# **Model: MKS-360AL**

### 700mm x 500mm x 720mm



Product Type: MKS-360AL	Ultrasound frequency: 40/28KHz
Liner material: SUS304t2.0mm	Capacity: 130L
Time control: digital control 0-30 minutes	Ultrasound power: 2160W 36head
Heating power: 2000W	Liner size: 650 * 450 * 450MM
Packing size: 835 * 580 * 855MM	Product Size: 700 * 500 * 720MM
G.W: 85kg	N.W: 65kg
Power: AC100-120v, 50 / 60HzAC220-240V, 50 / 60Hz	Power adjustment range: 900 – 2160W



# **Ultrasonic Cleaning Machine**

**Features** 



# Why Choose MKS Series Ultrasonic Cleaner



# **Ultrasonic Cleaning Machine**

**Stainless Steel Smart Cleaning Precision And Durability** 





### **Product Features**

**Ultrasonic Cleaning Machine** 

Can work 24 hours a day

1-inch large valve outlet can be ruled out large dirt

Industrial plate and professional industrial transducer (head)

Double-sided welding within the tank watertight

The generator driver is the latest sixth generation driver board in South Korea

Panel power, timing, temperature control for intelligent digital button control

Can be adjusted according to different cleaning different cleaning power

Optional frequency 20, 28, 40, 68, 80, 120 KHZ and other frequency.

### **Control Interface**

**Ultrasonic Cleaning Machine** 



### **Material**

### **Ultrasonic Cleaning Machine**



# **Double Insurance Design Safer**DOUBLE INSURANCE DESIGN MORE SECURE

**SAFETY** 

Safe Power Supply






**DURABLE** 

# Fan Cooling Long Time Cleaning Overheating Protection

**High Power Circuit Board** 



### **REAL SHOT**

### **Actual Pictures**



### **REAL SHOT**

**Actual Pictures** 



# **Parts List**



**Cleaning Basket** 



**Power Cable** 



**Ultrasonic Cleaner** 

# **Before And After Cleaning Effect Comparison**







Ultrasonic cleaning is based on cavitation. That is, rapid formation of micro bubbles in the cleaning fluid.



Micro-bubble cavitation produce implosion so that the cleaning object splatter stains down.

### **Service Attitude**

**Our Mission: Integrity, Service and Quality Assurance** 

We offer 100% quality guaranteed products.

- 1. 7 days return policy; product return are accepted within 7 days from received date of items, customer can return the products to us without any reason if the product has any quality issue not caused by improper handling. Buyer will cover both sides freight cost.
- 2. 1 Year Warranty; enjoy one year free warranty service. After-sales support; life-long maintenance and technical support service.

If products have any problem, please contact us immediately, we will send the spare parts to you according to the problem described and you can also send goods back to us for repair.

24 hours efficient delivery, we have a large quantity on stock. Delivery can be made for same day purchase order.

We can OEM a variety of Ultrasonic non-standard equipment.



# www.smtsplicetape.com www.ai-part.com

Contact us and request for Product Catalog with Price List